

King Safety Cables

When hose, couplings or clamps fail, or there is an accidental separation of the assembly, King safety cables minimize damage to equipment and injuries to operators. King safety cable reaches across the hose fittings to provide standby safety for hose. Spring-loaded loops in the cable ends open easily to pass over the couplings for a firm grip on the hose. Thoroughly tested with years of service. A positive safeguard for air hose connections - helps you meet today's safety standards. *King safety cable must be installed in the extended position (no slack).*



Features:

- hose-to-hose or hose-to-rigid outlet
- King cable is the low cost answer to eliminate injuries caused by broken air hose connections
- highly resistant to rust and corrosion
- no tools needed - Easy to install and remove



Hose End Tool End

Style WSR, for hose-to-tool service



Hose End Hose End

Style W, for hose-to-hose service

Cable	Hose ID	Length	Max. Work. Press. PSI	Steel Part #	Price/E	SS Part #	Price/E	Cable	Hose ID	Length	Max. Work. Press. PSI	Steel Part #	Price/E	SS Part #	Price/E
1/8"	1/2" - 1 1/4"	20 1/4"	200	WSR1	\$18.25	WSR1SS	\$47.75 ^{NEW}	1/8"	1/2" - 1 1/4"	20 1/4"	200	WB1	\$18.25	---	---
3/16"	1/2" - 2"	28"	200	WSR3	26.20	---	---	3/16"	1/2" - 2"	28"	200	WB3	27.05	---	---
1/4"	1 1/2" - 3"	38"	200	WSR2	28.80	WSR2SS	100.75 ^{NEW}	1/4"	1 1/2" - 3"	38 1/4"	200	WA2	29.70	WA2SS	\$106.00 ^{NEW}
3/8"	4"	44"	200	WSR4	63.75	---	---	3/8"	4"	44"	200	WA4	63.80	---	---

Note: Cables are shipped with safety restraint labels attached. Labels are not pictured.

King Safety Cable Options



WSR1E
WSR1E with stainless steel marine eye



WB1C
WB1 with safety clip and lanyard

Cable	Part #	Description	Max. Working Pressure PSI	Price/E
1/8"	WSR1C	WSR1 with safety clip and lanyard used to lock Air King couplings	200	\$31.75
1/8"	WB1C	WB1 with safety clip and lanyard used to lock Air King couplings	200	31.20
1/8"	WSR1E	WSR1 with stainless steel safety marine eye used to connect safety cable to a bolt on tool	200	52.70
1/4"	WA2B	WA2 with bronze/copper ferrule for special environmental conditions	200	59.50
1/8"	WB1SS	WB1 made with 304 stainless steel cable and springs with bronze/copper ferrules for special environmental conditions	200	50.50

See page 5 for OSHA regulations.

Spring Guard

NEW



Protects hose against the effects of flexing at its most vulnerable point - immediately behind the coupling. End 'tang' allows end guard to be secured under a clamp or ferrule. Made of half-round galvanized steel wire to fit hose OD's from 7/8" to 3".

Guard ID	Hose OD		Wire Gauge	Over All Length	Tang Length	Approx. # of Coils	Galvanized Steel Part #	Price/E
	From	To						
3/4"	7/8"	15/16"	0.175	12"	1"	33	SEGC1-0.75-12	\$9.00
1"	15/16"	1-1/4"	0.175	12"	1"	33	SEGC1-1.00-12	10.00
1 1/4"	1-1/4"	1-1/2"	0.175	14"	2"	39	SEGC1-1.25-14	12.00
1 1/2"	1-1/2"	1-3/4"	0.175	14"	2"	39	SEGC1-1.50-14	14.00
1 3/4"	1-3/4"	2"	0.175	16"	2"	44	SEGC1-1.75-16	16.00
2"	2"	2-1/2"	0.280	16"	2"	44	SEGC1-2.00-16	20.00
2 1/2"	2-1/2"	3"	0.280	18"	2"	50	SEGC1-2.50-18	25.00
3"	3"	3-1/4"	0.280	18"	2"	50	SEGC1-3.00-18	30.00