



Pressure Washer Hose

Creamery/Paper Mill Washdown

(Specification 3213B/3325T)

Without Nozzle (3213B)

Nom. I.D.		Nom. O.D.		Max. W.P.		Suction		Min. Bend Radius		Wt. Per Ft.		Standard Pack	Stock (X) or Minimum Order Qty.	Gates Item No.	List Price Per Ft.
(In.)	(mm)	(In.)	(mm)	(psi)	(MPa)	(In. Hg.)	(mm Hg)	(In.)	(mm)	(Lbs.)	(Kg)				
1/2	12.7	.91	23.1	200	1.38	25.0	635	5.0	127	.28	.13	REEL	X	3213-0401	\$2.73
3/4	19.1	1.25	31.8	200	1.38	15.0	381	6.0	152	.49	.22	50 ft.	X	3213-0413	3.91
3/4	19.1	1.25	31.8	200	1.38	15.0	381	6.0	152	.49	.22	REEL	X	3213-0501	3.91
1	25.4	1.52	38.6	200	1.38	15.0	381	8.0	203	.65	.30	50 ft.	X	3213-0416	5.63
1	25.4	1.52	38.6	200	1.38	15.0	381	8.0	203	.65	.30	REEL	25,000 ft.	3213-0415	5.63



With Nozzle (3325T)

Nom. I.D.		Nom. O.D.		Max. W.P.		Suction		Min. Bend Radius		Wt. Per Ft.		Standard Pack	Stock (X) or Minimum Order Qty.	Gates Item No.	List Price Per Ea.
(In.)	(mm)	(In.)	(mm)	(psi)	(MPa)	(In. Hg.)	(mm Hg)	(In.)	(mm)	(Lbs.)	(Kg)				
3/4	19.1	1.25	31.8	150	1.03	25.0	635	6.0	152	27.5	12.47	50 ft.	1 EA (X)	3213-0543	\$377.02
1	25.4	1.50	38.1	150	1.03	15.0	381	8.0	203	33.5	15.20	50 ft.	1 EA (X)	3213-0544	422.41
1-1/4	31.8	1.75	44.5	150	1.03	15.0	381	10.0	254	39.5	17.92	50 ft.	1 EA (X)	3213-0545	472.91

RECOMMENDED FOR: Cold and hot water up to 212°F (100°C) where steam is injected into the water. Used for paper mill, food handling or processing plant washdown service requiring hose with a **non-marking** cover.

CAUTION: NOT RECOMMENDED FOR USE WITH STEAM.

TEMPERATURE: -40°F to +212°F (-40°C to +100°C) continuous service.
-20°F to +180°F (-29°C to +82°C) continuous service. For nozzle only.

CONSTRUCTION: **Tube:** Type P (EPDM). Black.
Type D (SBR). Black. For nozzle only.
Reinforcement: Synthetic, high tensile textile cord.
Braided, high tensile synthetic textile cord. For nozzle only.
Cover: Type P (EPDM). White. All sizes are perforated on plain end hose only.
Type D (Natural Rubber). Gray with green stripe. For nozzle only.

HOSE ENDS: Plain. (3/4", 1" and 1-1/4" available with built-in nozzle, 24" long tapered to 1/2" I.D.)

COUPLINGS: 1, 14, 15 or 75 Gates GLX™ (For without nozzle only). Reference pages 120-133.

PACKAGING: 1/2": Packaged in 600' to 800' reels. Maximum 4 pieces. One length 25' to 50'.
Maximum of 2 lengths under 100'.
3/4" and 1": Packaged in 300' to 400' reels. Maximum 3 pieces. One length 25' to 50'.
Maximum of 2 lengths under 100'.
50' lengths (without nozzle) Packaged 50' coiled in a carton.
50' lengths (with nozzle) Packaged each length coiled and wrapped in polyethylene.

BRANDING: Continuous ink print label. Example: "WASHDOWN 3/4 INCH (19.1mm) 200 PSI (1.38Mpa) WP MADE IN U.S.A."
Continuous transfer label. Example: "WASHDOWN 3/4 INCH (19.1mm) 150 PSI (1.03Mpa) WP MADE IN MEXICO"

SPECIAL ORDER REQUIREMENTS: Special production runs require minimum order quantities of 25,000 feet for plain end hose and 600 feet for 3/4" through 1-1/4" with nozzle.

REMNANT LENGTHS: None.

Due to continual product improvements, Gates reserves the right to alter specs and prices without prior notice.

