



**Pressure Washer Hose**

**PowerClean™**

(Specification 3603PW, 4657, KB, KG, KK, KY, PB, PG, PY)

**PowerClean 2500 (4657, 4657PB, 4657PG, 4657PY)**

Color	Nom. I.D.		Nom. O.D.		Max. W.P.		Suction		Min. Bend Radius		Wt. Per Ft.		Standard Pack	Stock (X) or Minimum Order Qty.	Gates Item No.	List Price Per Ft.
	(In.)	(mm)	(In.)	(mm)	(psi)	(MPa)	(In. Hg)	(mm Hg)	(In.)	(mm)	(Lbs.)	(Kg)				
Black	1/2	12.7	.80	20.3	2500	17.24	30.0	762	7.0	178	.28	.13	LG. REEL	5000 ft.	4657-2412	\$2.64
Black	1/2	12.7	.80	20.3	2500	17.24	30.0	762	7.0	178	.28	.13	REEL	X	4657-2408	2.75
Blue	1/2	12.7	.80	20.3	2500	17.24	30.0	762	7.0	178	.28	.13	REEL	X	4657-2413	2.89
Gray	1/2	12.7	.80	20.3	2500	17.24	30.0	762	7.0	178	.28	.13	REEL	5000 ft.	4657-2414	2.89
Yellow	1/2	12.7	.80	20.3	2500	17.24	30.0	762	7.0	178	.28	.13	REEL	X	4657-2415	2.89

**PowerClean 3000 (4657, 4657PB, 4657PG, 4657PY)**

Black	3/8	9.5	.68	17.3	3000	20.68	30.0	762	5.0	127	.23	.10	LG. REEL	X	4657-2401	\$2.31
Black	3/8	9.5	.68	17.3	3000	20.68	30.0	762	5.0	127	.23	.10	REEL	X	4657-2402	2.40
Blue	3/8	9.5	.68	17.3	3000	20.68	30.0	762	5.0	127	.23	.10	LG. REEL	X	4657-2403	2.43
Blue	3/8	9.5	.68	17.3	3000	20.68	30.0	762	5.0	127	.23	.10	REEL	X	4657-2404	2.52
Gray	3/8	9.5	.68	17.3	3000	20.68	30.0	762	5.0	127	.23	.10	REEL	X	4657-2416	2.52
Yellow	3/8	9.5	.68	17.3	3000	20.68	30.0	762	5.0	127	.23	.10	REEL	X	4657-2417	2.52

**PowerClean 3500 (4657, 4657PB, 4657PG, 4657PY)**

Black	1/4	6.4	.53	13.5	3500	24.13	30.0	762	4.0	102	.15	.07	LG. REEL	X	4657-2418	\$1.92
Black	1/4	6.4	.53	13.5	3500	24.13	30.0	762	4.0	102	.15	.07	REEL	X	4657-2400	2.00
Blue	1/4	6.4	.53	13.5	3500	24.13	30.0	762	4.0	102	.15	.07	REEL	X	4657-2419	2.10
Gray	1/4	6.4	.53	13.5	3500	24.13	30.0	762	4.0	102	.15	.07	REEL	X	4657-2420	2.10
Yellow	1/4	6.4	.53	13.5	3500	24.13	30.0	762	4.0	102	.15	.07	REEL	5000 ft.	4657-2421	2.10

**PowerClean 3600 (3603PW)**

Black	5/16	7.9	.56	14.2	3600	24.80	30.0	762	5.0	127	.15	.07	REEL	X	3603-0011	\$2.30
-------	------	-----	-----	------	------	-------	------	-----	-----	-----	-----	-----	------	---	-----------	--------

**PowerClean 4000 (4657KK, 4657KB, 4657KG, 4657KY)**

Black	3/8	9.5	.68	17.3	4000	27.58	30.0	762	5.0	127	.23	.10	LG. REEL	X	4657-2405	\$2.78
Black	3/8	9.5	.68	17.3	4000	27.58	30.0	762	5.0	127	.23	.10	REEL	X	4657-2225	2.89
Blue	3/8	9.5	.68	17.3	4000	27.58	30.0	762	5.0	127	.23	.10	REEL	X	4657-2422	3.03
Gray	3/8	9.5	.68	17.3	4000	27.58	30.0	762	5.0	127	.23	.10	REEL	X	4657-2423	3.03
Yellow	3/8	9.5	.68	17.3	4000	27.58	30.0	762	5.0	127	.23	.10	REEL	5000 ft.	4657-2424	3.03

**RECOMMENDED FOR:** Heavy duty use on hot and cold water high pressure cleaning equipment where heavy duty service is required. Flexible. Use Bend Restrictors to extend service life. **NOTE: Not recommended for steam service.**

**TEMPERATURE:** -40°F to +250°F (-40°C to +121°C) Laboratory tested for normal service. Increased operating temperatures will reduce hose assembly service life.

**CONSTRUCTION:** **Tube:** Type C (Nitrile). Black. Specially compounded to handle high pressure water service.  
**Reinforcement:** High tensile steel one-wire braid.  
**Cover:** Type C<sub>2</sub> (Modified Nitrile). Black, Blue, Gray, Yellow. Specially compounded to handle pressure washer environment. (Blue, Gray and Yellow covers are non-marking).

**COUPLINGS:** 72 Gates permanent Power Crimp® or 74 MegaCrimp® couplings. Reference pages 122-133.

**PACKAGING:** 1/4" through 1/2": Packaged in 300' reels. Any number of pieces. All lengths in 50' increments. Minimum length 50'.  
1/4" through 1/2": Packaged in 1000' large reels. Any number of pieces. All lengths in 50' increments. Minimum length 50'.

**BRANDING:** Continuous ink brand. Example: "GATES 3/8 Inch PowerClean™ 3000 Max WP 3000 PSI Not For Steam Service Made In U.S.A."

**SPECIAL ORDER REQUIREMENTS:** Special production runs require minimum order quantities of 5,000 feet per size.

**REMNANT LENGTHS:** Remnant lengths are sometimes available in popular sizes at a discount. Contact Denver Industrial Hose Marketing for pricing, order requirements and availability.

Due to continual product improvements, Gates reserves the right to alter specs and prices without prior notice.



**Pressure Washer Hose**

**PowerClean™**  
(Specification 4657F, XB, XG, XY)

**PowerClean 4000 (4657F, 4657XB, 4657XG, 4657XY)**

Color	Nom. I.D.		Nom. O.D.		Max. W.P.		Suction		Min. Bend Radius		Wt. Per Ft.		Standard Pack	Stock (X) or Minimum Order Qty.	Gates Item No.	List Price Per Ft.
	(In.)	(mm)	(In.)	(mm)	(psi)	(MPa)	(In. Hg)	(mm Hg)	(In.)	(mm)	(Lbs.)	(Kg)				
Black	1/2	12.7	.86	21.8	4000	27.58	30.0	762	7.0	178	.42	.19	LG. REEL	5000 ft.	4657-2425	\$3.68
Black	1/2	12.7	.86	21.8	4000	27.58	30.0	762	7.0	178	.42	.19	REEL	X	4657-2426	3.83
Blue	1/2	12.7	.86	21.8	4000	27.58	30.0	762	7.0	178	.42	.19	REEL	5000 ft.	4657-2409	4.02
Gray	1/2	12.7	.86	21.8	4000	27.58	30.0	762	7.0	178	.42	.19	REEL	5000 ft.	4657-2427	4.02
Yellow	1/2	12.7	.86	21.8	4000	27.58	30.0	762	7.0	178	.42	.19	REEL	5000 ft.	4657-2428	4.02

**PowerClean 5000 (4657F, 4657XB, 4657XG, 4657XY)**

Black	3/8	9.5	.74	18.8	5000	34.47	30.0	762	5.0	127	.35	.16	LG. REEL	X	4657-2406	\$3.25
Black	3/8	9.5	.74	18.8	5000	34.47	30.0	762	5.0	127	.35	.16	REEL	X	4657-2407	3.38
Blue	3/8	9.5	.74	18.8	5000	34.47	30.0	762	5.0	127	.35	.16	REEL	X	4657-2429	3.55
Gray	3/8	9.5	.74	18.8	5000	34.47	30.0	762	5.0	127	.35	.16	REEL	5000 ft.	4657-2430	3.55
Yellow	3/8	9.5	.74	18.8	5000	34.47	30.0	762	5.0	127	.35	.16	REEL	5000 ft.	4657-2431	3.55

**PowerClean 6000 (4657F)**

Black	1/4	6.4	.59	15.0	6000	41.37	30.0	762	4.0	102	.25	.11	REEL	X	4657-2410	\$2.74
-------	-----	-----	-----	------	------	-------	------	-----	-----	-----	-----	-----	------	---	-----------	--------

**RECOMMENDED FOR:** Heavy duty use on hot and cold water high pressure cleaning equipment where heavy duty service is required. Flexible. Use Bend Restrictors to extend service life. **NOTE: Not recommended for steam service.**

**TEMPERATURE:** -40°F to +250°F (-40°C to +121°C) Laboratory tested for normal service. Increased operating temperatures will reduce hose assembly service life.

**CONSTRUCTION:** **Tube:** Type C (Nitrile). Black. Specially compounded to handle high pressure water service.  
**Reinforcement:** High tensile steel two-wire braid.  
**Cover:** Type C<sub>2</sub> (Modified Nitrile). Black, Blue, Gray, Yellow. Specially compounded to handle pressure washer environment. (Blue, Gray and Yellow covers are non-marking).

**COUPLINGS:** Gates permanent Power Crimp® or MegaCrimp® couplings. Reference pages 122-133.

**PACKAGING:** 1/4" through 1/2": Packaged in 300' reels. Any number of pieces. All lengths in 50' increments. Minimum length 50'.  
3/8" and 1/2": Packaged in 1000' large reels. Any number of pieces. All lengths in 50' increments. Minimum length 50'.

**BRANDING:** Continuous ink brand. Example: " GATES 3/8 Inch PowerClean™ 5000 Max WP 5000 PSI Not For Steam Service Made In U.S.A."

**SPECIAL ORDER REQUIREMENTS:**

Special production runs require minimum order quantities of 5,000 feet per size.

**REMNANT LENGTHS:**

Remnant lengths are sometimes available in popular sizes at a discount. Contact Denver Industrial Hose Marketing for pricing, order requirements and availability.

Due to continual product improvements, Gates reserves the right to alter specs and prices without prior notice.



**Pressure Washer Hose**

**Pressure Washer Assemblies**  
(Specification 3603PW)

Nom. I.D.		Nom. O.D.		Max. W.P.		Suction		Min. Bend Radius		Wt. Per Ea.		Standard Pack	Stock (X) or Minimum Order Qty.	Gates Item No.	List Price Per Ea.
(In.)	(mm)	(In.)	(mm)	(psi)	(MPa)	(In. Hg)	(mm Hg)	(In.)	(mm)	(Lbs.)	(Kg)				
1/4	6.4	.48	12.2	3000	20.68	30.0	762	4.0	102	5.50	2.50	50 ft.	5 EA (X)	3604-0034	\$114.58
3/8	9.5	.63	16.0	3000	20.68	30.0	762	5.0	127	8.50	3.86	50 ft.	5 EA (X)	3604-0035	127.82
1/2	12.7	.76	19.3	3000	20.68	30.0	762	7.0	178	11.50	5.22	50 ft.	5 EA (X)	3604-0036	148.12

**RECOMMENDED FOR:** Standard duty use on hot and cold water high pressure cleaning equipment. Extremely flexible, lightweight and easy to handle. **NOTE: Not recommended for steam service.**

**TEMPERATURE:** -40°F to +250°F (-40°C to +121°C). Laboratory tested for normal service. Increased operating temperatures will reduce hose assembly service life.

**CONSTRUCTION:** **Tube:** Type C (Nitrile). Black. Specially compounded to handle high pressure water service.  
**Reinforcement:** High tensile steel one-wire braid.  
**Cover:** Type C<sub>2</sub> (Modified Nitrile). Black. Specially compounded to handle pressure washer environment. Bend restrictors applied on each end.

**COUPLINGS:** Gates permanent couplings (MP/MPX). Factory coupled assemblies only.

**PACKAGING:** 1/4" through 1/2": Coiled in a carton, 5 assemblies per carton.

**BRANDING:** Continuous ink brand. Example: "GATES 3/8 Inch Pressure Washer Max 3000 PSI Not For Steam Service Made In Mexico"

**SPECIAL ORDER REQUIREMENTS:** Special production runs require minimum order quantities of 5,000 feet per size.

**REMNANT LENGTHS:** None

