



**Industrial Hose
Products/List Prices**



39496-000
July 30, 2007
Supersedes 39496-000
July 1, 2006

Material Handling Hose

609W

(Dry Cement Delivery)

(Specification 3129F, 3129H, 3129L)

1/8" Tube Thickness (3129L)

Nom. I.D.		Nom. O.D.		Max. W.P.		Suction		Min. Bend Radius		Wt. Per Ft.		Standard Pack	Stock (X) or Minimum Order Qty.	Gates Item No.	List Price Per Ft.
(In.)	(mm)	(In.)	(mm)	(psi)	(MPa)	(In. Hg)	(mm Hg)	(In.)	(mm)	(Lbs.)	(Kg)	Pack	Order Qty.	Item No.	Per Ft.
3	76.2	3.47	88.1	40	.28	—	—	36.0	914	1.30	.59	100 ft.	X	3129-0660	\$17.34
4	101.6	4.47	113.5	40	.28	—	—	48.0	1219	1.69	.77	100 ft.	X	3129-0670	20.19
4-1/2	114.3	4.97	126.2	35	.24	—	—	54.0	1372	1.89	.86	100 ft.	X	3129-0675	21.81
5	127.0	5.47	138.9	30	.21	—	—	60.0	1524	2.09	.95	100 ft.	X	3129-0680	23.86
6	152.4	6.47	164.3	25	.17	—	—	72.0	1829	2.48	1.13	100 ft.	X	3129-0690	28.52
6-5/8	168.3	7.10	180.3	20	.14	—	—	72.0	1829	2.73	1.24	100 ft.	200 ft.	3129-0700	32.11

3/16" Tube Thickness (3129H)

Nom. I.D.		Nom. O.D.		Max. W.P.		Suction		Min. Bend Radius		Wt. Per Ft.		Standard Pack	Stock (X) or Minimum Order Qty.	Gates Item No.	List Price Per Ft.
(In.)	(mm)	(In.)	(mm)	(psi)	(MPa)	(In. Hg)	(mm Hg)	(In.)	(mm)	(Lbs.)	(Kg)	Pack	Order Qty.	Item No.	Per Ft.
4	101.6	4.61	117.1	60	.41	—	—	48.0	1219	2.21	1.00	100 ft.	X	3129-0790	\$23.22

1/4" Tube Thickness (3129F)

Nom. I.D.		Nom. O.D.		Max. W.P.		Suction		Min. Bend Radius		Wt. Per Ft.		Standard Pack	Stock (X) or Minimum Order Qty.	Gates Item No.	List Price Per Ft.
(In.)	(mm)	(In.)	(mm)	(psi)	(MPa)	(In. Hg)	(mm Hg)	(In.)	(mm)	(Lbs.)	(Kg)	Pack	Order Qty.	Item No.	Per Ft.
4	101.6	4.73	120.1	60	.41	—	—	48.0	1219	2.69	1.22	100 ft.	X	3129-0570	\$26.25

RECOMMENDED FOR: Pneumatic transfer of bulk cement and other dry bulk materials.

TEMPERATURE: -40°F to +150°F (-40°C to +66°C) continuous service.

CONSTRUCTION: **Tube:** Type D₃ (Natural Rubber). Black. Static conductive.

Reinforcement: Synthetic, high tensile textile.

Cover: Type D (SBR). Black with gray spiral stripe.

COUPLINGS: , or . Reference pages 122-133.

PACKAGING: 100' length coiled and wrapped in polyethylene.

BRANDING: Continuous transfer label. Example: "Gates 609W Dry Cement Delivery — Static Conductive Tube 40 PSI (.28MPa) WP Made In U.S.A."

SPECIAL ORDER REQUIREMENTS:

Special production runs require minimum order quantities of 400 feet for sizes through 4" and 200 feet for sizes above 4". If a special transfer label is required, contact Denver Industrial Hose Marketing for minimum quantity.

Specific cut lengths available through the Cut Length Program. Contact Customer Service for details.

REMNANT LENGTHS: Remnant lengths are sometimes available in popular sizes at a discount. Contact Denver Industrial Hose Marketing for pricing, order requirements and availability.

Due to continual product improvements, Gates reserves the right to alter specs and prices without prior notice.



**Industrial Hose
Products/List Prices**



39496-000
July 30, 2007
Supersedes 39496-000
July 1, 2006

Material Handling Hose

**688SB
(Bulk Commodity)
(Specification 4691L)**

Nom. I.D.		Nom. O.D.		Max. W.P.		Suction		Min. Bend Radius		Wt. Per Ft.		Standard	Stock (X) or Minimum	Gates	List Price
(in.)	(mm)	(in.)	(mm)	(psi)	(MPa)	(in. Hg)	(mm Hg)	(in.)	(mm)	(Lbs.)	(Kg)	Pack	Order Qty.	Item No.	Per Ft.
2	50.8	2.77	70.4	60	.41	30.0	762	16.0	406	1.65	.75	100 ft.	X	4691-0305	\$24.70
2	50.8	2.77	70.4	60	.41	30.0	762	16.0	406	1.65	.75	200 ft.	400 ft.	4691-0306	24.70
3	76.2	3.81	96.8	60	.41	30.0	762	24.0	610	2.54	1.15	100 ft.	X	4691-0325	33.91
4	101.6	4.77	121.2	45	.31	30.0	762	32.0	813	3.21	1.46	100 ft.	X	4691-0340	44.26
4	101.6	4.77	121.2	45	.31	30.0	762	32.0	813	3.21	1.46	200 ft.	400 ft.	4691-4342	44.26
4-1/2	114.3	5.27	133.9	40	.28	30.0	762	36.0	914	3.57	1.62	50 ft.	X	4691-0355	52.66
5	127.0	5.77	146.6	40	.28	30.0	762	40.0	1016	3.93	1.78	50 ft.	X	4691-0360	57.20
6	152.4	6.76	171.7	40	.28	30.0	762	48.0	1219	4.65	2.11	50 ft.	X	4691-0346	62.23
6	152.4	6.76	171.7	40	.28	30.0	762	48.0	1219	4.65	2.11	200 ft.	400 ft.	4691-0349	62.23

RECOMMENDED FOR: Transfer of bulk materials via suction, gravity or pneumatic systems where abrasion resistance is the primary requirement. Examples: Dry cement, sand, gravel, feed, seed and slurries.

TEMPERATURE: -40°F to +150°F (-40°C to +66°C) continuous service.

CONSTRUCTION: **Tube:** Type D₃ (Natural Rubber). Black. Static conductive. 3/16" thick.
Reinforcement: Synthetic, high tensile textile with steel wire helix.
Cover: Type D (SBR). Black corrugated with gray spiral stripe.

COUPLINGS: , , or . Reference pages 122-133.

PACKAGING: All lengths coiled and wrapped in polyethylene.

BRANDING: Continuous transfer label. Example: 688SB Wet-Dry Bulk Commodity 60 PSI (.41MPa) WP Made In U.S.A."

SPECIAL ORDER REQUIREMENTS: Special production runs require minimum order quantities of 400 feet for sizes through 4" and 200 feet for sizes above 4". If a special transfer label is required, contact Denver Industrial Hose Marketing for minimum quantity.

Specific cut lengths available through the Cut Length Program. Contact Customer Service for details.

REMNANT LENGTHS: Remnant lengths are sometimes available in popular sizes at a discount. Contact Denver Industrial Hose Marketing for pricing, order requirements and availability.

