



**Industrial Hose  
Products/List Prices**



39496-000  
July 30, 2007  
Supersedes 39496-000  
July 1, 2006

**Water Hose**

**Marlin®**

(Specification 3137M)

Nom. I.D.		Nom. O.D.		Max. W.P.		Suction		Min. Bend Radius		Wt. Per Ft.		Standard	Stock (X) or Minimum Order Qty.	Gates Item No.	List Price Per Ft.
(In.)	(mm)	(In.)	(mm)	(psi)	(MPa)	(In. Hg.)	(mm Hg)	(In.)	(mm)	(Lbs.)	(Kg)	Pack			
1-1/2	38.1	1.82	46.2	150	1.03	—	—	12.0	305	.47	.21	100 ft.	X	3137-0370	\$6.54
1-1/2	38.1	1.90	48.3	150	1.03	—	—	12.0	305	.63	.29	100 ft.	X	3137-0371	8.74
2	50.8	2.33	59.2	150	1.03	—	—	20.0	508	.65	.30	100 ft.	X	3137-0372	7.20
2	50.8	2.41	61.2	150	1.03	—	—	20.0	508	.84	.38	100 ft.	X	3137-0373	9.72
2-1/2	63.5	2.83	71.9	150	1.03	—	—	25.0	635	.80	.36	100 ft.	400 ft.	3137-0374	10.14
2-1/2	63.5	2.91	73.9	150	1.03	—	—	25.0	635	1.02	.46	100 ft.	X	3137-0375	13.98
3	76.2	3.33	84.6	150	1.03	—	—	36.0	914	.95	.43	100 ft.	X	3137-0376	10.17
3	76.2	3.41	86.6	150	1.03	—	—	36.0	914	1.21	.55	100 ft.	X	3137-0377	16.22
3-1/2	88.9	3.91	99.3	150	1.03	—	—	42.0	1067	1.47	.67	100 ft.	X	3137-0378	20.50
4	101.6	4.33	110.0	150	1.03	—	—	47.6	1219	1.32	.60	100 ft.	X	3137-0379	12.81
4	101.6	4.33	110.0	150	1.03	—	—	47.6	1219	1.32	.60	200 ft.	400 ft.	3137-1272	12.81
4	101.6	4.41	112.0	150	1.03	—	—	47.6	1219	1.67	.76	100 ft.	X	3137-0380	24.12
5	127.0	5.44	138.2	150	1.03	—	—	60.0	1524	2.17	.98	100 ft.	X	3137-0381	29.82
6	152.4	6.40	162.6	150	1.03	—	—	72.0	1829	2.32	1.05	100 ft.	X	3137-0382	35.57
6	152.4	6.49	164.9	150	1.03	—	—	72.0	1829	2.96	1.34	100 ft.	X	3137-0383	49.79

**RECOMMENDED FOR:** Water discharge in heavy duty service requiring a compact, rugged and lightweight hose.

**TEMPERATURE:** -40°F to +180°F (-40°C to +82°C) continuous service.

**CONSTRUCTION:** **Tube:** Type P (EPDM). Black.  
**Reinforcement:** Multiple plies of synthetic, high tensile textile.  
**Cover:** Type D (SBR). Black with green spiral stripe.

**COUPLINGS:** . Reference pages 122-133.

**PACKAGING:** 100' coiled and wrapped in polyethylene.

**BRANDING:** Continuous transfer label. Example: Marlin® Water Discharge 150 PSI (1.03MPa) WP Made In U.S.A."

**SPECIAL ORDER REQUIREMENTS:** Special production runs require minimum order quantities of 400 feet for sizes through 4" and 200 feet for sizes above 4". If a special transfer label is required, contact Denver Industrial Hose Marketing for minimum quantity.

**Specific cut lengths available through the Cut Length Program. Contact Customer Service for details.**

**REMNANT LENGTHS:** Remnant lengths are sometimes available in popular sizes at a discount. Contact Denver Industrial Hose Marketing for pricing, order requirements and availability.

Due to continual product improvements, Gates reserves the right to alter specs and prices without prior notice.





**Industrial Hose  
Products/List Prices**



39496-000  
July 30, 2007  
Supersedes 39496-000  
July 1, 2006

**Water Hose**

**Dolphin®**

(Specification 3137T)

Nom. I.D.		Nom. O.D.		Max. W.P.		Suction		Min. Bend Radius		Wt. Per Ft.		Standard Pack	Stock (X) or Minimum Order Qty.	Gates Item No.	List Price Per Ft.
(In.)	(mm)	(In.)	(mm)	(psi)	(MPa)	(In. Hg.)	(mm Hg.)	(In.)	(mm)	(Lbs.)	(Kg)				
1-1/4	31.8	1.53	38.9	150	1.03	—	—	—	—	.37	.17	100 ft.	X	3137-0884	\$5.35
1-1/2	38.1	1.78	45.2	150	1.03	—	—	—	—	.43	.20	100 ft.	X	3137-0883	5.85
1-1/2	38.1	1.78	45.2	150	1.03	—	—	—	—	.43	.20	200 ft.	X	3137-0898	5.85
2	50.8	2.32	58.9	150	1.03	—	—	—	—	.65	.30	100 ft.	X	3137-0885	6.50
2	50.8	2.32	58.9	150	1.03	—	—	—	—	.65	.30	200 ft.	X	3137-0905	6.50
2-1/2	63.5	2.82	71.6	150	1.03	—	—	—	—	.80	.36	100 ft.	X	3137-0888	8.45
3	76.2	3.36	85.3	150	1.03	—	—	—	—	1.08	.49	100 ft.	X	3137-0886	8.45
3	76.2	3.36	85.3	150	1.03	—	—	—	—	1.08	.49	200 ft.	X	3137-0895	9.50
4	101.6	4.36	111.7	150	1.03	—	—	—	—	1.41	.64	100 ft.	X	3137-0889	12.55
4	101.6	4.36	111.7	150	1.03	—	—	—	—	1.41	.64	200 ft.	X	3137-0896	12.55
6	152.4	6.38	162.1	125	.86	—	—	—	—	2.09	.95	100 ft.	X	3137-0890	22.20
6	152.4	6.38	162.1	125	.86	—	—	—	—	2.09	.95	200 ft.	X	3137-0892	22.20

**RECOMMENDED FOR:** Medium to light duty water discharge for agricultural, construction and industrial applications. EPDM tube designed to handle a variety of liquids including Lasso\*, Lasso II\* and Freedom\*.

**TEMPERATURE:** -40°F to +180°F (-40°C to +82°C).

**CONSTRUCTION:** **Tube:** Type P (EPDM). Black.  
**Reinforcement:** Synthetic, high tensile textile.  
**Cover:** Type P (EPDM). Black with green spiral stripe.

**COUPLINGS:** [5], [6], [7], [8] or [49], all sizes. Reference pages 122-133.

**NOTE: 3:1 Safety Factor for Burst Pressure to Working Pressure is reduced when the temperature increases.**

**PACKAGING:** 100' length coiled and wrapped in polyethylene.

**BRANDING:** Continuous transfer label. Example: Dolphin® Water Discharge 150 PSI (1.03MPa) WP Made In U.S.A."

**SPECIAL ORDER REQUIREMENTS:** Special production runs require minimum order quantities of 400 feet for sizes through 4" I.D. and 200 feet for sizes above 4" I.D. If a special transfer label is required, contact Denver Industrial Hose Marketing for minimum quantity.

**Specific cut lengths available through the Cut Length Program. Contact Customer Service for details.**

**REMNANT LENGTHS:** Remnant lengths are sometimes available in popular sizes at a discount. Contact Denver Industrial Hose Marketing for pricing, order requirements and availability.

\* Registered trademarks of Monsanto.

Due to continual product improvements, Gates reserves the right to alter specs and prices without prior notice.