# Type B

#### Application:

· used primarily on irrigation and suction lines

#### Features:

- · hot dipped, galvanized
- has a double pin locking lever for smooth closing action
- Type B (Bauer style) locks on the male side
- Each coupler is equipped with a safety pin to prevent accidental openings.
- These fittings are not recommended for chemicals or any hazardous type materials where the possibility of leakage would result in health or environmental concerns. Consult Dixon® for recommendations.



## Male x Hose Shank

Size	Galvanized Steel Part #
2"	MC3092
3"	MC3093
4"	MC3094
6"	MC3096
8"	MC3098
10"	MC30910 <sup>1</sup>
12"	MC30912 <sup>1</sup>



## **Male with Male NPT**

Size	Galvanized Steel Part #
2"	MCM3112
3"	MCM3113
4"	MCM3114
6"	MCM3116
8"	MCM3118



## Female x Hose Shank

#### Feature:

· supplied with gasket

Size	Galvanized Steel Part #
2"	FC3102
3"	FC3103
4"	FC3104
6"	FC3106
8"	FC3108
10"	FC31010
12"	FC31012



#### **Female with Male NPT**

#### Feature:

· supplied with gasket

Size	Galvanized Steel Part #
2" 3" 4" 6" 8"	FCM3122 FCM3123 FCM3124 FCM3126 FCM3128





<sup>&</sup>lt;sup>1</sup> 10" and 12" supplied with ACB304 lever assist bar on page 261