



™

Kuriyama of America, Inc.

360 E. State Parkway
Schaumburg, IL 60173-5335 USA

Phone: (847) 755-0360

Toll-Free FAX: (800) 800-0320

International FAX: (847) 885-0996 **Email:** sales@kuriyama.com

Series No. A1687-08X400, Kuri Tec® A1687 Series 1/2 in. Nominal ID and 400 ft Standard Coil Lengths 800 PSI PVC/Polyurethane Blend Reinforced Spray Hose

Unique PVC/polyurethane blended core provides excellent resistance to hydrocarbon-based tree spray, lawn care and pest control chemicals. Reinforced with high tensile strength yarn. PVC ribbed cover provides abrasion resistance.

Performance-Plus Three Year Warranty!

Tree Spraying



[Construction](#) | [Features](#) | [Applications](#) | [Service Temperature Range](#) | [Specifications](#) | [Nominal Specifications](#) | [Note](#) | [Compliance Footnotes](#)

Construction

Tube	Black PVC/Polyurethane Blend
Reinforcement	High Tensile Strength Yarn Two-Pass Spiral Construction
Cover	Ribbed PVC

Features

- Extremely tough and kink resistant.
- PVC/polyurethane blended core - provides better chemical resistance than comparable all-PVC hoses.
- Ribbed cover provides excellent abrasion-resistance.

Features

- 800 PSI working pressure.
- Pin-pricked cover vents vapor . . . helps prevent ballooning.
- Silicone-free.
- One-piece lengths.
- Phthalate Free!

Applications

Application

- Tree and orchard spraying.
- Agricultural spraying.
- Commercial weed spraying.

Service Temperature Range

Service Temperature [Max]

15 °F
-10 °C

Service Temperature [Min]

160 °F
70 °C

Specifications

Brand

Kuri Tec®

Series

A1687

Type

Reinforced Spray Hose

Style

800 PSI Blend Reinforced Spray Hose

Performance

PVC/Polyurethane Core Provides Excellent Chemical Resistance

Nominal Specifications

Size Code

08

Nominal ID	1/2 in 12.7 mm
Nominal OD	0.850 in 21.6 mm
Max. Working Pressure at 70°F (20°C)	800 psi
Max. Working Pressure at 122°F (50°C)	450 psi
Standard Coil Lengths	400 ft
Approx. Weight. Per Pkg.	90 lb
Spiral Construction	2-Pass

Note

-

Note

Note : Use of hydraulic or reusable-type fittings are not recommended for coupling Kuri Tec® hose products. Hose claims involving use of these fittings will be disallowed.

Compliance Footnotes

-

Compliance Footnotes

Phthalate Free - Manufactured from all phthalate free material